

**AMENDMENTS TO THE CLAIMS:**

This listing of claims will replace all prior versions and listings of claims in the application:

1. (Currently Amended) An information processing apparatus comprising:  
a first display device which displays a ~~pointer~~ main operation screen;  
a second display device which ~~displays a virtual screen including a screen of the~~  
~~first display device~~ comprises a touch pad; and  
a display controller which ~~moves the~~ displays a pointer on the main operation  
screen, a position of the pointer being changed by the touch pad, to a pointed position  
~~in the virtual screen of the second display device~~ the display controller configured to:  
display a virtual screen including the main operation screen, and  
change a position of the main operation screen in the virtual screen based  
on a change of the position of the pointer caused by the touch pad.
2. (Currently Amended) The apparatus according to claim 1, wherein when the  
~~pointed~~ position of the pointer is changed to a position which is out of the main  
operation screen ~~of the first display device~~, the display controller changes ~~a display the~~  
position of the ~~first display device~~ main operation screen in the virtual screen to a  
position which is out of the main operation screen.
3. (Currently Amended) The apparatus according to claim 1, wherein ~~after~~ when  
the position of the pointer has been moved changed, the display controller stops display  
of the virtual screen on the second display device.

4. (Original) The apparatus according to claim 1, wherein  
the second display device has a switching function; and  
the display controller stops display of the virtual screen when the switching  
function is operated in a state where the virtual screen is displayed.

5. (Currently Amended) The apparatus according to claim 1, wherein when the  
~~pointed~~ position of the pointer is changed to a position which is out of the main  
operation screen ~~of the first display device~~, the display controller changes the position of  
the main operation screen ~~of the first display device~~ in the virtual screen in accordance  
with relative positions of the virtual screen and the ~~pointed position~~ pointer.

6. (Currently Amended) The apparatus according to claim 1, wherein when the  
~~pointed~~ position of the pointer is changed to a position which is out of the main  
operation screen ~~of the first display device~~, the display controller changes the position of  
the main operation screen ~~of the first display device~~ in the virtual screen in such a  
manner that relative positions of the ~~displayed image of the first display device~~ main  
operation screen and the pointer before the pointer has been ~~moved~~ changed is  
maintained.

7. (Currently Amended) The apparatus according to claim 1, wherein when the  
~~pointed~~ position of the pointer is changed to a position which is out of the main  
operation screen ~~of the first display device~~, the display controller changes the position of  
the main operation screen ~~of the first display device~~ in the virtual screen so that the  
pointer is displayed at a fixed position in the main operation screen ~~of the first display~~  
~~device~~.

8. (Currently Amended) The apparatus according to claim 1, wherein the display controller makes the second display device display the virtual screen indicating the main operation screen ~~of the first display device~~ in the virtual screen and the position of the pointer.

9. (Currently Amended) A control method ~~of operating pointing device for an information processing apparatus comprising a first display device which displays a main operation screen, a second display device which comprises a touch pad, and a display controller which displays a pointer on the main operation screen, a position of the pointer being changed by the touch pad~~, comprising:

~~displaying a screen on which an operation based on a pointer is enabled on a first display device;~~

displaying a virtual screen including the main operation screen ~~of the first display device~~ on ~~[[a]]~~ the second display device; and

~~moving the pointer to a pointed position in the virtual screen of the second display device based on a pointing operation on the virtual screen~~ changing a position of the main operation screen in the virtual screen based on a change of the position of the pointer caused by the touch pad.

10. (Currently Amended) The control method according to claim 9, further comprising, when the ~~pointed~~ position of the pointer is changed to a position which is out of the main operation screen of the first display device, changing a display the position of the main operation screen first display device in the virtual screen to a position which is out of the main operation screen.

11. (Currently Amended) The control method according to claim 9, further comprising, ~~after~~ when the position of the pointer has been ~~moved~~ changed, stopping display of the virtual screen on the second display device.

12. (Currently Amended) The control method according to claim 9, wherein the second display device has a switching function; and further comprising:  
stopping a display of the virtual screen when the switching function is operated in a state where the virtual screen is displayed.

13. (Currently Amended) The control method according to claim 9, further comprising, when the ~~pointed~~ position of the pointer is changed to a position which is out of the main operation screen ~~of the first display device~~, changing the position of the main operation screen ~~of the first display device~~ in the virtual screen in accordance with relative positions of the virtual screen and the ~~pointed position~~ pointer.

14. (Currently Amended) The control method according to claim 9, further comprising, when the ~~pointed~~ position of the pointer is changed to a position which is out of the main operation screen ~~of the first display device~~, changing the position of the main operation screen ~~of the first display device~~ in the virtual screen in such a manner that relative positions of the ~~displayed image of the first display device~~ main operation screen and the pointer before the pointer has been ~~moved~~ changed is maintained.

15. (Currently Amended) The control method according to claim 9, further comprising, when the ~~pointed~~ position of the pointer is changed to a position which is out of the main operation screen ~~of the first display device~~, changing the main operation

screen ~~of the first display device~~ in the virtual screen so that the pointer is displayed at a fixed position in the main operation screen ~~of the first display device~~.

16. (Currently Amended) The control method according to claim 9, further comprising making the second display device display the virtual screen indicating the main operation screen ~~of the first display device~~ in the virtual screen and the position of the pointer.